

Bright Ideas

D.D.E., Inc.

H.I.D. Light Fixture Tester

Simply screw in and turn on the power. Internal lamps indicate if the starter (ignitor), the ballast, or the lamp needs replacement. Tester is available in two models.

Medium Base (E26, E27) up to 150 watts -
Mogul Base (E39, E40) up to 1000 watts -

Can be used on High Pressure Sodium, Metal Halide and Mercury Vapor fixtures.



Reflector Kits:

These reflector kits are designed to be used for the delamping of existing fixtures. They are available in five different configurations designed for various fixture sizes. All kits contains the following components specifically designed for a particular size fixture.

- 1 Silverlux® Reflector
- 2 Relocation Brackets
- 4 Lamp Sockets
- All necessary hardware required for installation.
- Complete Installation Instructions.

To assure proper fit of reflectors in existing fixtures a preinstallation inspection by a 3M Authorized Silverlux® Manufacturer is necessary. Other reflectors are available. Please contact DISC at **1-800-DLA-BULB** for further information.

Fixture Size	No. of Lamps (From/To)	Lamp Length	National Stock Number
2X4	4 to 3	4'	6210-01-394-5465
2X4	4 to 2	4'	6210-01-384-1496
1X4	2 to 1	4'	6210-01-384-1427
2X2	4 to 2	2'	6210-01-384-1385
4' Strip	2 to 1	4'	6210-01-384-1576
8' Strip	2 to 1	8'	6210-01-384-1505

Silverlux® is a registered trademark of 3M. Information provided by 3M.

Analog Light Meter
National Stock Number: 6695-01-250-4864
Dimensions: 2.5"W X 2.75"H X 0.75"D.
Slide switch selects one of three linear scales: 10-50fc, 50-250fc, or 200-1000fc.
Correction for the color quality of light.
Cosine correction for the incident angle of light.
Latest taut band suspension.
Weight: 4 oz
No battery required.

Digital Light Meter
National Stock Number: 6695-01-354-3018
Dimensions: 2.5"W X 3.87"H X 1.062"D.
One digital scale: 0-1999fc
Cosine-correction for the incident angle of light.
ON/OFF: ON when cover is open, OFF when cover is closed.
1/2" high black numerals on light background.
Data hold function for easy readout.
Weight: 4 oz
9v battery required; nominal battery life is 1000 hours of continuous use.