

PHOTOLUMINESCENT EXIT SIGNS

Non Radioactive ♦ Non Electrical ♦ Standard or Directional

LOW LEVEL EXIT MARKER KICK PLATE

MODEL # CE18100XS

Specifications

Marker Size:	Standard sizes Height: 10" Weight: 34", 40", 46" Custom sizes available
Letter size:	1" stroke with 6" height
Letter color:	Green illuminating
Background:	Brushed Aluminum, Stainless Steel or Brass Finish
Mounting:	Specify type of door for attachment - wood, glass or aluminum
Activation:	3-5 foot-candles ambient lighting
Directional:	Optional field applied arrows
Life expectancy:	Twenty-five years+
Construction:	Stenciled aluminum or stainless steel with photo-luminescent text
Maintenance:	None
Attributes:	Non-electrical, non-radioactive, explosion proof, ASTM E 162 Flame spread Index., 22.88
Listing Reports:	Underwriters Laboratories Listed Pursuant to Standard UL1994. Low Level Pathway & Low Level Exit Markings California State fire Marshal Listing #6210-1371:1 01 San Francisco Research Report and Product Approval # 10440ACT, Los Angeles Research Report and Product Approval #RR-25083-T, US Test Report #182556-1, ICBO listing # 5101



**Contains no
Tritium !**

Special Order Item Only

Contact the DSCP Lighting Team for additional information on cost and availability.

1-800-DLA-BULB

(1-800-352-2852)



CORPORATE ENERGY MANAGEMENT SYSTEMS, INC.