

Electronic Fluorescent Ballasts

GENERAL ELECTRIC

LAMP TYPE	VOLTS	# OF LAMPS	INPUT WATTS	BALLAST FACTOR	MIN START TEMP F	THD	NSN FSC 6250	GE PART #
PARALLEL INSTANT START BALLASTS FOR 270MA F32T8 LAMP								
F32T8	120	1	33	87.5	0	<10%	01-353-7722	G1-IN-T8-D-1
F32T8	120	2	59	87.5	0	<10%	01-364-8906	G2-IN-T8-D-120
F32T8	120	3	85	87.5	0	<10%	01-364-2997	G3-IN-T8-120
F32T8	120	4	112	87.5	0	<10%	01-364-2999	G4-IN-T8-120
F32T8	120	1	31	88	0	<10%		
F32T8	120	2	59	88	0	<10%		
F32T8	120	3	87	88	0	<10%		
F32T8	120	4	114	88	50	<10%		
F32T8	277	1	33	87.5	0	<10%	01-353-7723	G1-IN-T8-D-277
F32T8	277	2	59	87.5	0	<10%	01-364-8908	G2-IN-T8-D-277
F32T8	277	3	84	87.5	0	<10%	01-364-2998	G3-IN-T8-277
F32T8	277	4	111	87.5	0	<10%	01-365-0987	G4-IN-T8-277
F32T8	277	1	31	88	0	<10%		
F32T8	277	2	59	88	0	<10%		
F32T8	277	3	87	88	0	<10%		
F32T8	277	4	114	88	50	<10%		
PARALLEL INSTANT START BALLASTS FOR 265MA F96T8 LAMPS								
F96T8	120	2	105	85	50	<10%	01-377-7376	G2-IL-T8-8FT-120
F96T8	120	2	113	88	50	<10%		
F96T8	277	2	113	88	50	<10%	01-440-3597	G2-IL-T8-8FT-277
F96T8	277	1	113	88	50	<10%		
SERIES RAPID START BALLASTS FOR 430MA F40T12, F40T10, F30T12 AND CORRESPONDING U-TUBE LAMPS								
	120	1	30-33	84-87	60	<20%	01-440-3607	G1-RN-T12-ILL-120
	120	2	60	83-87	60	<20%	01-440-3609	G2-RN-T12-ILL-120
	120	3	87-93	83-87	60	<20%	01-440-3610	G3-RN-T12-ILL-120
	277	1	30-34	84-89	60	<20%	01-440-3615	G1-RN-T12-ILL-277
	277	2	60	83-87	60	<20%	01-440-3620	G2-RN-T12-ILL-277
	277	3	87-93	83-88	60	<20%	01-440-3622	G3-RN-T12-ILL-277