Occupancy Sensors

Sensor Switch, Inc.					
MFG P/N	Nomenclature	Volts	Time Delay	Coverage	NSN
PP-20	Power Pack	120/277 VAC	N/A	N/A	6210-01-443-4482
PP-20-2P	Power Pack	120/277 VAC	N/A	N/A	6210-01-443-4485
HM-10-R	(PIR) High Mount	12 to 24 VAC/VDC	30 sec to 20 min	up to 130 ft	6210-01-443-4475
SP-20	Slave Pack	120/277 VAC	N/A	N/A	6210-01-443-4507
PP-2pm	Momentary Power Pack for lighting contractor interface	120/277 VAC	N/A	N/A	6210-01-443-4511
CM-ALC	Ambient Light Sensor for Dimming Ballast	10 VDC	N/A	N/A	6210-01-443-4534
CM-PHX	Photocell Sensor	15 VDC	N/A	N/A	6210-01-411-6689
WSD-RR7-I	(PIR) Decorator Wall Switch	21 to 36 VAC	30 sec to 20 min	900 sq ft @ 180 degrees	6210-01-443-4549
LWS-RR7-I	(PIR) Wall Switch	24 VAC	30 sec to 20 min	40 ft @ 180 degrees	6210-01-443-4555
LWS-PDT-RR7-I	(PIR & Microphonics) Wall Switch	24 VAC	30 sec to 20 min	40 ft @ 180 degrees	6210-01-443-4557
CM-RR7	(PIR) Celing Mount	24 VAC	30 sec to 20 min	360 degrees	6210-01-443-4561
CM-PDT-RR7	(PIR & Microphonics) Ceiling Mount	24 VAC	30 sec to 20 min	360 degrees	6210-01-443-4568
WV-RR7	(PIR) Wall & Corner Mount	24 VAC	30 sec to 20 min	40 ft @ 180 degrees	6210-01-443-4571
WV-PDT-RR7	(PIR & Microphonics) Wall Corner Mount	24 VAC	30 sec to 20 min	40 ft @ 180 degrees	6210-01-443-4582
WSD-I	(PIR) Wall Mount	120/277 VAC	30 sec to 20 min	50 ft @ 180 degrees	6210-01-411-6684
WSD-W	(PIR) Wall Mount	120/277 VAC	30 sec to 20 mon	50 ft @ 180 degrees	6210-01-411-6681
LWS-PDT-I	(PIR & Microphonics) Wall Mount	120/277 VAC	30 sec to 20 min	2000 sq ft @ 180 degrees	6210-01-443-3947
LWS-PDF-2P-I	(PIR & Microphonics) Wall Mount	120/277 VAC	30 sec to 20 min	2000 sp ft @ 180 degrees	6210-01-443-3982
CM R-9	(PIR) Ceiling Mount	120/277 VAC	30 sec to 20 min	900 sq ft	6210-01-443-4103
CMR-PDT	(PIR & Microphonics)	120/277 VAC	30 sec to 20 min	2000 sq ft	6210-01-443-4109
WVR-16	(PIR) Wall Mount	120/277 VAC	30 sec to 20 min	1600 sq ft @ 120 degrees	6210-01-443-4116*
WVR-16-2P	(PIR) Wall Mount	120/277 VAC	30 sec to 20 min	1600 sq ft @ 120 degrees	6210-01-443-4186
WVR-PDT	(PIR & Microphonics) Wall Mount	120/277 VAC	30 sec to 20 min	2000 sp ft @ 180 degrees	6210-01-443-4220
WVR-PDT-2P	(PIR & Microphonics)	120/277 VAC	30 sec to 20 min	2000 sq ft @ 80 degrees	6210-01-443-4290
CM-9-R-P	(PIR) Ceiling Mount	12 to 24 VAC/VDC	30 sec to 20 min	360 degrees	6210-01-443-4360
CM-PDT-R-P	(PIR & Microphonics)	12 to 24 AC/VDC	30 sec to 20 min	360 degrees	6210-01-443-4445
WV-16-R-P	(PIR) Wall Mount	12 to 24 VAC/VDC	30 sec to 20 min	40 ft @ 120 degrees	6210-01-443-4458
WV-PDT-R-P	(PIR & Microphonics)	12 to 24 VAC/VDC	30 sec to 20 min	40 ft @ 120degrees	6210-01-443-4461
HW-BR	(PIR) Hallway	12 to 24 VAC/VDC	30 sec to 20 min	up to 130 ft	6210-01-443-4464

Occupancy Sensors

sensorswitch™

WALL SWITCH DECORATOR SENSORS

DESCRIPTION	MODEL NUMBER	NSN
Wall Switch Decorator Sensor 120/277 VAC; 800/1200 Watts Color: Ivory; (White)	**WSD-I** **WSD-W**	6210-01-411-6684 6210-01-411-6681

LARGE AREA WALL SWITCH SENSORS

Large Area Wall Switch Microphonic - Dual Technology 120/277 VAC; 13 Amps Color:Ivory -2 Pole Unit	**LWS-PDT -I** **LWS-PDT- 2P**	6210-01-443-3947 6210-01-443-3982

LINE VOLTAGE SENSORS

Volumetric Wide View Sensor 120/277 VAC; 13 Amps Mt. Height 8 Ft. - 2 Pole Unit	**WVR-16** **WVR-16- 2P**	6210-01-443-4116 6210-01-443-4186
Volumetric Wide View Sensor Microphonic - Dual Technology 120/277 VAC; 13 Amps Mt. Height 8 Ft. - 2 Pole Unit	**WVR-PDT** **WVR-PDT- 2P**	6210-01-443-4220 6210-01-443-4290
Ceiling Mount Sensor 120/277 VAC; 800/1200 Watts Mt. Height up to 12 Ft.	**CMR-9**	6210-01-443-4103
Ceiling Mount Sensor Microphonic - Dual Technology 120/277 VAC; 800/1200 Watts Mt. Height up to 12 Ft.	**CMR-PDT**	6210-01-443-4109

sensorswitch™

POWER PACKS & SLAVE PACKS

DESCRIPTION	MODEL NUMBER	NSN
Power Pack 10 to 40 VDC 120/277 VAC; 20 amps	**PP-20**	6210-01-443-4482
2 Pole Power Pack	**PP-20-2P**	6210-01-443-4485
Slave Pack	**SP-20**	6210-01-443-4507
Power Pack with Momentary Contacts	**PP-2PM**	6210-01-443-4511



LOW VOLTAGE SENSOR HEADS

Ceiling Mount Sensor 10 to 40 VDC/VAC Mt Height up to 12 Ft. - Isolated Relay & Photocell	**CM-9- R-P**	6210-01-443-4360
Ceiling Mount Sensor Microphonic - Dual Technology 10 to 40 VDC/VAC MT Height up to 12 Ft. - Isolated Relay & Photocell	**CM-PDT- R-P**	6210-01-443-4445
Wide View Sensor 10 TO 40 VDC/VAC Coverage: 120 Deg. by 40 Ft. - Isolated Relay & Photocell	**WV-16- R-P**	6210-01-443-4458
Wide View Sensor Microphonic - Dual Technology 10 to 40 VDC/VAC Coverage: 120 Deg. by 40 Ft. - Isolated Relay & Photocell	**WV-PDT- R-P**	6210-01-443-4461
Hallway Sensor 10 to 40 VDC/VAC Coverage: 130 Linear Ft. - Isolated Relay	**HW-13-R**	6210-01-443-4464
Warehouse Aislway Sensor 10 to 40 VDC/VAC Coverage: 100 Linear Ft. - Isolated Relay	**HW-10-R**	6210-01-443-4475