

Portable Lighting

WESTERN TECHNOLOGY

4100 "SITE LIGHT"

Three Directional Area Light with 5.25 inch 150 lbs. pull magnetic mounts, uses standard par 38, 50 watt maximum lamp. Constructed of durable Polytech. Optional Steel Protective Lamp guard #4105-3 offers additional protection against bulb breakage.



Product Number	Description	NSN
4 1 0 0 - 2 5	Lamp unit with 25 ft cord	6 2 3 0 - 0 1 - 4 6 2 - 8 5 2 8
4 1 0 0 - 5 0	Lamp unit with 50 ft cord	6 2 3 0 - 0 1 - 4 6 2 - 8 5 2 9
4 1 0 0 - 1 0 0	Lamp unit with 100 ft cord	6 2 3 0 - 0 1 - 4 6 2 - 8 5 3 0
4 1 0 5 - 3	Protective Lamp guard	6 2 3 0 - 0 1 - 4 6 2 - 8 5 2 5

4200 "SITE LIGHT"

Single Outlet Par Lamp Holder with 5.25 inch 150 lbs. pull magnetic fixed mount uses standard par 38, 150 watt maximum lamp with retainer ring #4105-1, or any par 38, 250 watt lamp with optional retainer ring #4105-2.



Product Number	Description	NSN
4 2 0 0 - 2 5	Lamp unit with 25 ft cord	6 2 3 0 - 0 1 - 4 6 2 - 8 5 3 3
4 1 0 5 - 2	Support Ring Blue 250 Watt Max	6 2 3 0 - 0 1 - 4 6 2 - 8 5 3 4
4 1 0 5 - 3	Protective Lamp guard	6 2 3 0 - 0 1 - 4 6 2 - 8 5 2 5

Portable Lighting

WESTERN TECHNOLOGY

4210 "SITE LIGHT"

Single Outlet Par Lamp Holder with large handle and removable 5.25 inch 150 lbs. pull magnetic swivel mount, uses standard par 38, 150 watt maximum lamp with retainer ring #4105-1, or any par 38, 250 watt lamp with optional retainer ring #4105-2.



Product Number	Description	NSN
4210-25	Lamp unit with 25 ft cord	6230-01-462-8531
4210-50	Lamp unit with 50 ft cord	6230-01-462-8532
4210-25-WPTLP-12V	Lamp unit with 25 ft water proof twist lock plug connectorized cord. 12 volt rated	
14/2-25 WPTLP-12	25 ft 14/2 Extension cord with a water proof twist lock plug connector	
4127-4	4 Outlet step down transformer for 12 volt operation	
4105-2	Support Ring Blue 250 Watt Max	6230-01-462-8534
4105-3	Protective Lamp guard	6230-01-462-8525
Duralight 12V	12 volt par 38 flood lamp	