






# FIXTURES



 Lamp:LU250  
 Lumens:27500  
 Input Wattage:305  
 Spacing Criteria:2.0



 Lamp:MH400/U  
 Lumens:36000  
 Input Wattage:460  
 Spacing Criteria:2.0



## 16" Acrylic High Bay



### Features

Heavy duty, die cast aluminum housing with white powder coat finish. White powder coated junction box with threaded hole for hook or pendant mount applications. New bracket design for easy reflector adjustment to achieve different photometric patterns. The acrylic reflector has a 92.5 total luminaire efficiency and is best suited for light colored ceilings due to its inherent upright components.

### Applications

Indoor ceiling heights exceeding 15'. Such as large retail stores, warehouse facilities, commercial buildings, where there is a light colored ceiling.

### Electrical

U. L. Listed for dry locations.

### Options

Wire Guard  
Quartz restrike  
Glass Lense



Part#	Wattage/Lamp	NSN
<b>Standard Fixture Products</b>		
High Pressure Sodium		
NWLT150HPSACHB16	150 /HPS	
NWLT200HPSACHB16	200 /HPS	
NWLT250HPSACHB16	250 /HPS	
NWLT400HPSACHB16	400 /HPS	
Metal Halide		
NWLT175MHACHB16	175 /MH	
NWLT250MHACHB16	250 /MH	
<b>Pulse Start Fixture Products</b>		
NWLT320MHACHB/PS/16	320 /MH	
NWLT350MHACHB/PS/16	350 /MH	

Pulse Start Comparison		
MH320/PS 34,000 lumens 106 lpw	VS	MH400 36,000 lumens 90 lpw
MH350/PS 38,000 lumens 109 lpw		MS400/BU 40,000 lumens 100 lpw