Incandescent Lamps

A-19
A-21


R-20
R-30


ER-30

LAMP WATTS	BULB	BASE	FINISH AND SERVICE	AVG LIFE (HOURS)	LUMENS	VOLTS	NATIONAL STOCK NUMBER
15/135/150	A-21	3 CONT. MED	3-WAY, SOFT WHITE	1200	80/2200/2300	120	6240-01-344-507-1
27	R-20	MEDIUM	CLEAR	2000	N/A	120	6240-01-344-507-2
34	A-19	MEDIUM	INSIDE FROSTED	1500	410	120	6240-01-345-608-1
				1500	410	130	6240-01-344-480-1
			INSIDE FROSTED, LONG LIFE	2500	365	120	6240-01-345-224-1
				2500	365	130	6240-01-344-480-2
			CLEAR, LONG LIFE	4500	345	120	6240-01-358-605-6
42	ER-30	MEDIUM	FLOOD, LONG LIFE	9000	600CP	120	6240-01-358-372-8
45	R-20	MEDIUM	SPOT	2000	N/A	120	6240-01-344-477-3 §
	R-30	MEDIUM	FLOOD	2000	485	120	6240-01-344-478-3 §
50	ER-30	MEDIUM	INSIDE FROSTED (I2,I4,I5) INSIDE FROSTED	2000	525	120	6240-01-168-157-8
				2000	525	130	6240-01-196-698-2
			PINK (I2,I4,I5)	2000	525	120	6240-01-344-508-1 §
50/135/185	A-21	3 CONT.MED	3 WAY (I3)	1200	588/2330/2910	120	6240-01-344-992-5
52	A-19	MEDIUM	CLEAR	1000	800	120	6240-01-344-513-6
				1000	800	130	6240-01-298-324-6
			INSIDE FROSTED	1000	800	120	6240-01-344-478-0
				1000	800	130	6240-01-024-637-0
			INSIDE FROSTED, LONG LIFE	2500	700	120	6240-00-617-174-0
				2500	700	130	6240-01-344-514-8
54	A-19	MEDIUM	CLEAR, LONG LIFE	4500	640	120	6240-01-358-605-1
			INSIDE FROSTED, LONG LIFE	4500	640	120	6240-01-019-034-8
			BRITE-WHITE, LONG LIFE	4500	610	120	6240-01-358-605-2
55	A-19	MEDIUM	CLEAR	1000	810	120	6240-01-344-478-2 §

Footnotes p.51.
All operating and physical characteristics for items in this section were provided by the manufacturers of these products.
§ Item will be available until stock has been depleted.

Incandescent Lamps

A-19


ER-30


R-20
R-30


PAR-38

LAMP WATTS	BULB	BASE	FINISH AND SERVICE	AVG LIFE (HOURS)	LUMENS	VOLTS	NATIONAL STOCK NUMBER	
64	ER-30	MEDIUM	FLOOD, LONG LIFE	9000	1050CP	120	6240-01-358-372-9	
65	(HRG) PAR-38	MED SKIRT	SPOT, (I1,I4,I6)	2000	675	120	6240-01-168-157-7	
				2000	675	130	6240-01-344-478-8	
			FLOOD, (I1,I4,I6)	2000	675	120	6240-01-344-505-3	
				2000	675	130	6240-01-344-478-5	
	R-30	MEDIUM	SPOT	2000	770	120	6240-01-344-479-2	
	R-20	MEDIUM	FLOOD	2000	770	120	6240-01-344-479-1	
67	A-19	MEDIUM	CLEAR	750	1130	120	6240-01-344-947-6	
				750	1130	130	6240-01-344-947-7	
			INSIDE FROSTED	750	1130	120	6240-01-344-377-9	
				750	1130	130	6240-01-344-378-0	
			INSIDE FROSTED, LONG LIFE	2500	930	120	6240-01-279-760-6	
				2500	930	130	6240-01-168-157-6	
			CLEAR, LONG LIFE	4500	810	120	6240-01-358-605-3	
			INSIDE FROSTED, LONG LIFE	4500	775	120	6240-01-358-605-4	
70	A-19	MEDIUM	INSIDE FROSTED (I7)	750	1140	120	6240-01-344-947-4	§
75	ER-30	MEDIUM	INSIDE FROSTED (I2,I4,I5)	2000	850	120	6240-01-089-614-8	
				2000	850	130	6240-01-196-698-4	
85	PAR-38	MED SKIRT	SPOT (I3,I5,I7)	2000	930	120	6240-01-344-479-4	
				2000	930	130	6240-01-344-479-5	
			FLOOD, PROJECTOR (I3,I5,I7)	2000	930	120	6240-01-344-479-3	§
			SILICONE AMBER (I3,I5,I7)	2000	N/A	120	6240-01-344-480-4	§
			SILICONE BLUE (I3,I5,I7)	2000	N/A	120	6240-01-344-480-5	§
			PAR SILICONE GREEN (I3,I5,I7)	2000	N/A	120	6240-01-344-480-7	§
			PAR SILICONE PINK (I3,I5,I7)	2000	N/A	120	6240-01-344-480-8	§
			PAR SILICONE RED (I3,I5,I7)	2000	N/A	120	6240-01-258-629-7	§
			PAR SILICONE YELLOW (I3,I5,I7)	2000	N/A	120	6240-01-344-480-9	§

Footnotes p.51
§ Item will be available until stock has been depleted.
All operating and physical characteristics for items in this section were provided by the manufacturers of these products.

Incandescent Lamps

A-19


R-40


ER-30
ER-40


PAR-38

LAMP WATTS	BULB	BASE	FINISH AND SERVICE	AVG LIFE (HOURS)	LUMENS	VOLTS	NATIONAL STOCK NUMBER
86	ER-30	MEDIUM	FLOOD, LONG LIFE	9000	1500CP	120	6240-01-358-711-2
	ER-40		FLOOD, LONG LIFE	9000	1200CP	120	6240-01-358-373-0
90	A-19	MEDIUM	CLEAR	750	N/A	120	6240-01-312-914-7
			CLEAR	750	N/A	130	6240-01-344-543-5
			INSIDE FROSTED	750	1620	120	6240-01-344-543-3
			INSIDE FROSTED	750	N/A	130	6240-01-157-511-4
			INSIDE FROSTED, LONG LIFE	2500	1360	120	6240-01-344-543-4
			INSIDE FROSTED, LONG LIFE	2500	1360	130	6240-01-098-013-0
			CLEAR, LONG LIFE	4500	1210	120	6240-01-358-605-5
	A-21	MEDIUM	INDUSTRIAL SERVICE, FROSTED	3500	1090	130	6240-01-344-544-9
95	A-19	MEDIUM	CLEAR	750	1620	120	6240-01-344-506-4 §
120	ER-40	MEDIUM	INSIDE FROSTED (I2, I4, I5)	2000	1475	120	6240-01-196-698-1
				2000	1475	130	6240-01-196-698-3
	(HRG) PAR-38	MED SKIRT	SPOT, (I1, I3, I5, I7)	2000	1500	120	6240-01-310-423-0
				2000	1420	130	6240-01-344-543-2
			FLOOD, (I1, I3, I5, I7)	2000	1370	120	6240-01-311-974-1
				2000	1420	130	6240-01-344-543-8
	R-40	MEDIUM	SPOT (I2, I3, I4, I5)	2000	1600	120	6240-01-344-505-9
				2000	1600	130	6240-01-344-506-0
			FLOOD (I2, I3, I4, I5)	2000	1600	120	6240-01-344-505-5
				2000	1600	130	6240-01-344-505-8
128	ER-40	MEDIUM	FLOOD, LONG LIFE	9000	2050CP	120	6240-01-358-373-1
135	A-21	MEDIUM	CLEAR	750	2580	120	6240-01-344-479-6
				750	2580	130	6240-01-344-479-7
			INSIDE FROSTED	750	2580	120	6240-01-344-506-2
				750	2580	130	6240-01-344-506-3
			CLEAR LONG LIFE	2500	2145	120	6240-01-344-479-9
				2500	2145	130	6240-01-344-480-0

§ Item will be available until stock has been depleted.
All operating and physical characteristics for items in this section were provided by the manufacturers of these products.

Incandescent Lamps

A-19
A-21



T-3

LAMP WATTS	BULB	BASE	FINISH AND SERVICE	AVG LIFE (HOURS)	LUMENS	VOLTS	NATIONAL STOCK NUMBER
135	A-21	MEDIUM	INSIDE FROSTED, LONG LIFE	2500	2145	120	6240-01-344-479-8
				2500	2145	130	6240-01-344-696-9
	A-19	MEDIUM	CLEAR, LONG LIFE	4500	1900	120	6240-01-358-605-7
			INSIDE FROSTED, LONG LIFE	4500	1900	120	6240-01-074-655-0
185	A-21	MEDIUM	INSIDE FROSTED	4500	2900	120	6240-01-358-605-8
Quartz Lamps							
350	T-3	RSC	CLEAR, HORIZONTAL BURNING POSITION	2000	10000	120	6240-01-344-514-3
				2000	9600	130	6240-01-344-514-4
900				2000	32000	240	6240-01-344-514-5
				2000	32000	277	6240-01-344-514-6
Traffic Signal Lamps							
54	A-21	MEDIUM	CLEAR	8000	530	120	6240-01-344-513-7
				8000	530	130	6240-01-344-513-8
	A-19			8000	550	120	6240-01-358-605-9
60	A-21	MEDIUM	CLEAR	8000	610	120	6240-01-344-481-2
				8000	610	130	6240-01-344-481-3
90	A-21	MEDIUM	CLEAR	8000	1040	130	6240-01-344-477-8
135	A-21	MEDIUM	CLEAR	7000	1750	120	6240-01-344-514-1
				7000	1750	130	6240-01-344-514-2
				8000	1750	120	6240-01-358-606-0

Incandescent Lamp Footnotes:

(I1) According to manufacturers these lamps will not meet the minimum requirements of the National Energy Policy Act of 1992 and will no longer be manufactured after the specified date.
(I2) Avoid contact of hot glass bulb with liquid or metal, as glass may shatter.
(I3) In base-up position heat may eventually deteriorate paper-lined or plastic sockets.
(I4) Should not be used in equipment where the base temperature will exceed 500 degrees Farenheit.
(I5) Avoid use at short distances on materials that are inflammable or susceptible to heat damage.
(I6) If lamp is cracked or broken, replace immediately. The lamp may continue to operate but the inner bulb may shatter.
(I7) Under moist conditions, metal parts of lamp and lampholder may become a shock hazard. Therefore, disconnect from circuit before touching.

All operating and physical characteristics for items in this section were provided by the manufacturers of these products.