

Compact Fluorescent Lamps*



GEN IV™ COLLECTION.

CFL'S, and now the GEN IV Collection. GEN IV is technologically superior, it has skipped an entire generation of compact fluorescent lamps.

In fact, these 14-watt GEN IV lamps are an efficient way to light sockets once traditionally reserved for 60-watt incandescent lamps and thereby significantly reducing operating costs.

Another key feature is the GEN IV lamp's 14-watt color - 2800k to provide a soft warm glow comparable to incandescent light, and 5000k to provide a cool light that imitates a phase of daylight.

All of this performance is packaged in a compact size design that allows for a convenient fit in a variety of fixtures.



EFA

EFD

- **Consumes 75% less energy than incandescent**
- **Generates less heat, reducing air conditioning load**
- **10,000 hour rated service life**
- **Low-profile pocket size to fit a more variety of fixtures (EFA 4 3/4 X 2 1/8 EFD 4 7/16 X 1 11/16)**
- **Light Weight**
- **Starting Temperature is as low as minus 22 degrees F**
- **Reliable electronic operation**
- **Lights instantly, no flicker**
- **Quick run-up time, approx. 40% of lumen after 3 Sec.**
- **Outstanding lumen maintenance, keeps approx. 80% of lumen after 4000 hours**
- **Approved for totally enclosed fixtures**
- **Approved for damp location**

Ordering Code	Shape	Rated Power (W)	Incan. Equiv. (W)	Initial Lumen (lm)	Rated Life (Hrs)	Color Temp.	CRI	Energy Star	NSN
EFA14E28	Pear	14	60	840	10,000	2800K	84	Yes	6240-01-482-3998
EFA14E50	Pear	14	60	840	10,000	5000K	88	Yes	6240-01-482-3275
EFD14E28	Delta 3 U tube	14	60	840	10,000	2800K	84	Yes	6240-01-482-3999
EFD14E50	Delta 3 U tube	14	60	800	10,000	5000K	88	Yes	6240-01-482-3273