

SECTION C

This document covers emergency drinking water for use by the Department of Defense as a component of operational rations.

C-1 ITEM DESCRIPTION

PACKAGING REQUIREMENTS AND QUALITY ASSURANCE PROVISIONS FOR CID A-A-20332B, WATER, DRINKING, EMERGENCY

Type, Size and Class.

Type I - Disposable pouch
Size A - 118 ml (4.0 fl. oz)
Class 1 – Thermoprocessed
Size B - 125 ml (4.2 fl. oz.)
Class 1 - Thermoprocessed

Type II - Rigid plastic container
Size A – 473.18 ml (16.0 fl. oz)
Class 3 - Other

C-2 PERFORMANCE REQUIREMENTS

A. Product standard. A sample shall be subjected to first article or product demonstration model inspection, as applicable, in accordance with the tests and inspections of Section E of this Packaging Requirements and Quality Assurance Provisions document.

B. Palatability and overall appearance. The finished product shall be equal to or better than the approved product standard in palatability and overall appearance.

SECTION D

D-1 PACKAGING

A. Flexible pouch.

(1) Pouch material. The preformed pouches shall be fabricated from 60 gauge biaxially oriented nylon laminated or extrusion coated to minimum 0.00035 inch thick

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

aluminum foil which is then laminated to 0.0007 inch thick modified polypropylene sealant layer. The polyolefin layer of bag material shall be suitably formulated for hot fill or post-fill processing. The material shall show no evidence of delamination, degradation, or foreign odor when heat-sealed or fabricated into pouches. The material shall be suitably formulated for food packaging and shall not impart an odor or flavor to the product. The complete exterior surface of the pouch shall be uniformly colored in the range of 20219, 30219, 30227, 30279, 30313, 30324, or 30450 of FED-STD-595, Colors Used in Government Procurement.

(2) Pouch construction. The pouch shall be a flat style preformed pouch having minimum inside dimensions of 4 inches wide by 7 inches long. The pouch shall be designed to provide a spout that extends approximately 1-1/2 inches on one end of pouch. The pouch shall be made by heat-sealing three edges with 3/8-inch (-1/8 inch, +3/16 inch) wide seals. The heat seals shall be made in a manner that will assure hermetic seals. The seals shall have an average seal strength of not less than 6 pounds per inch of width and no individual specimen shall have a seal strength of less than 5 pounds per inch of width when tested as specified in E-6,A,(4),a. Alternatively, the pouch shall exhibit no rupture or seal separation greater than 1/16 inch when tested for internal pressure resistance as specified in E-6,A,(4),c. A tear notch shall be provided on one or two edges of the pouch in the spout area. A 1/8-inch wide lip may be incorporated at the open end of the pouch to facilitate opening and filling of the pouch.

(3) Pouch filling and sealing. When specified, either 118 ml (4 fl. oz) or 125 ml (4.2 fl. oz.) of water shall be filled into the pouch and the filled pouch shall be sealed. The filled and processed pouch shall be buoyant in fresh water. The closure seal shall be free of foldover wrinkles or entrapped matter that reduces the effective closure seal width to less than 1/16 inch. Seals shall be free of impression or design on the seal surface that would conceal or impair visual detection of seal defects. The average seal strength shall be not less than 6 pounds per inch of width and no individual specimen shall have a seal strength of less than 5 pounds per inch of width when tested as specified in E-6,A,(4),b. Alternatively, the filled and sealed pouch shall exhibit no rupture or seal separation greater than 1/16 inch or seal separation that reduces the effective closure seal width to less than 1/16 inch when tested for internal pressure resistance as specified in E-6,A,(4),c. Filled and sealed pouch shall not leak when tested in accordance with E-6,A,(5). Filled and sealed pouch shall not be damaged when subjected to the 10-foot drop test in E-6,A,(6).

B. Plastic bottle.

(1) Material and construction. The material shall show no evidence of delamination, degradation, or foreign odor when fabricated into bottles. A square shape is preferred. The

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

material shall be suitably formulated for food packaging and shall not impart an odor or flavor to the product. The cap shall provide a hermetic seal, have a positive locking design that will not loosen by vibration, and shall be recloseable.

(2) Bottle filling and sealing. The bottle shall be filled with 473.18 ml (16.0 fl. oz) of water and hermetically closed with a cap. The filled bottle shall be buoyant in fresh water. Filled and sealed bottle shall not leak when tested in accordance with E-6,A,(5). Filled and sealed bottle shall not be damaged when subjected to the 10-foot drop test in E-6,A,(6).

D-2 LABELING

A. Pouches and bottles. Each pouch and bottle shall be clearly printed with permanent black ink or other, dark, contrasting color which is free of carcinogenic elements. The information may be located anywhere on the pouch or bottle (in one complete print), except the closure seal area. The label shall contain the following information:

EMERGENCY DRINKING WATER (letters not less than 1/8 inch high)
Net Volume
Contractor's name and address
Date 1/
Lot number

1/ Each pouch or bottle shall have the date of pack noted by using a four digit code beginning with the final digit of the current year followed by the three digit Julian day code. For example, 17 September 2003 would be coded as 3260. The Julian day code shall represent the day the product was packaged into the pouch or bottle.

D-3 PACKING

A. Packing.

(1) Pouches. Twenty-four pouches shall be packed in an intermediate fiberboard box. Two intermediate boxes shall be packed in a box constructed in accordance with style RSC, V3c of ASTM D 5118/D 5118M – 95 (2001), Standard Practice for Fabrication of Fiberboard Shipping Boxes. Each container shall be securely closed in accordance with ASTM D 1974-98 (2003), Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes.

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

(2) Bottles. Not more than 40 pounds of product shall be packed in a box constructed in accordance with style RSC-L, V3c of ASTM D 5118/D 5118M-95 (2001). Each container shall be securely closed in accordance with ASTM D 1974-98 (2003).

D-4 UNITIZATION

A. Unit loads. Boxes shall be arranged in unit loads in accordance with DSCP FORM 3507, Loads, Unit; Preparation for Semiperishable Subsistence Items.

D-5 MARKING

A. Shipping containers and unit loads. Shipping containers and unit loads shall be marked in accordance with DSCP FORM 3556, Marking Instructions for Boxes, Sacks and Unit Loads of Perishable and Semiperishable Subsistence.

SECTION E INSPECTION AND ACCEPTANCE

The following quality assurance criteria, utilizing ANSI/ASQC Z1.4-1993, Sampling Procedures and Tables for Inspection by Attributes, are required. When required, the manufacturer shall provide the certificate(s) of conformance to the appropriate inspection activity. Certificate(s) of conformance not provided shall be cause for rejection of the lot.

A. Definitions.

(1) Critical defect. A critical defect is a defect that judgment and experience indicate would result in hazardous or unsafe conditions for individuals using, maintaining, or depending on the item; or a defect that judgment and experience indicate is likely to prevent the performance of the major end item, i.e., the consumption of the ration.

(2) Major defect. A major defect is a defect, other than critical, that is likely to result in failure, or to reduce materially the usability of the unit of product for its intended purpose.

(3) Minor defect. A minor defect is a defect that is not likely to reduce materially the usability of the unit of product for its intended purpose, or is a departure from established standards having little bearing on the effective use or operation of the unit.

B. Classification of inspections. The inspection requirements specified herein are classified as follows:

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

(1) Product standard inspection. The first article or product demonstration model shall be inspected in accordance with the provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the performance requirements or any appearance or palatability failure shall be cause for rejection of the lot. The approved first article or product demonstration model shall be used as the product standard for periodic review evaluations. The DCMAO shall select sample units during production of contracts and submit them to the following address for evaluation:

US Army Soldier & Biological Chemical Command
Soldiers System Ctr., Natick Soldier Center
Attn: AMSRD-NSC-CF-F
15 Kansas Street
Natick, MA 01760-5018

One lot shall be randomly selected during each calendar month of production. Six (6) sample units of each item produced shall be randomly selected from that one production lot. The six (6) sample units shall be shipped to Natick within two (2) working days upon completion of all DCMAO inspection requirements. The sample units will be evaluated for the characteristics of appearance, odor, flavor, texture and overall quality.

(2) Conformance inspection. Conformance inspection shall include the examinations and methods of inspection cited in this section.

E-5 QUALITY ASSURANCE PROVISIONS (PRODUCT)

A. Product examination. The finished product shall be examined for compliance with the performance requirements specified in A-A-20332B. Finished product not equal to or better than the approved product standard in overall appearance and palatability shall be cause for rejection of the lot.

B. Methods of inspection.

(1) Shelf life. The contractor shall provide a certificate of conformance that the product has a 5-year shelf life when stored at 80°F.

(2) Net volume. The net volume shall be determined by measuring water in a graduated cylinder. Results shall be reported to the nearest 3 ml (0.1 ounce).

E-6 QUALITY ASSURANCE PROVISIONS (PACKAGING AND PACKING MATERIALS)

A. Packaging.

(1) Pouch material certification. Material listed below may be accepted on the basis of a contractor's certification of conformance to the indicated requirements. In addition, compliance to the requirements for inside pouch dimensions and dimensions of manufacturer's seals may be verified by certificate of conformance.

Requirement	Requirement paragraph	Test procedure
Thickness of films for laminated material	D-1, A,(1)	ASTM D 2103 <u>1/</u>
Aluminum foil thickness	D-1, A,(1)	ASTM B 479 <u>2/</u>
Laminated material identification and construction	D-1, A,(1)	Laboratory evaluation
Color of laminated material	D-1, A,(1)	Visual evaluation by FED-STD-595 <u>3/</u>

1/ ASTM D 2103-97 Standard Specification for Polyethylene Film and Sheeting

2/ ASTM B 479-00 Specification for Annealed Aluminum and Aluminum Alloy Foil for Flexible Barrier, Food Contact, and Other Applications

3/ FED-STD-595 Colors Used in Government Procurement

(2) Unfilled preformed pouch or bottle certification. A certification of conformance may be accepted as evidence that unfilled pouches or bottles conform to the requirements specified in D-1,A. When deemed necessary by the USDA, testing of the unfilled preformed pouches for seal strength shall be as specified in E-6,A,(4),a.

(3) Filled and sealed pouch or bottle examination. The filled and closed pouches or bottles shall be examined for the defects listed in table I. The lot size shall be expressed in pouches or bottles. The sample unit shall be one pouch or bottle. The inspection level shall be

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 0.65 for major defects and 2.5 for minor defects.

TABLE I. Filled and sealed pouch or bottle defects 1/

<u>Category</u>		<u>Defect</u>
<u>Major</u>	<u>Minor</u>	
101		Tear, hole, or open seal.
102		Unclean. <u>2/</u>
103		Does not pass the 10-foot drop test.
104		Foreign odor.
105		Leakage.
106		Not buoyant in fresh water.
	201	Label missing, incorrect, or illegible.
	202	Net volume less than required.
		<u>Pouches only</u>
107		Delamination. <u>4/</u>
108		Seal width less than 1/16 inch. <u>3/</u>
109		Not heat sealed on four sides.
	203	Tear notch missing.
	204	Delamination. <u>4/</u>
110		Pouch does not have spout.

1/ Any evidence of rodent or insect infestation shall be cause for rejection of the lot.

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

2/ Outer packaging shall be free from foreign matter which is unwholesome, has the potential to cause package damage (for example, glass, metal filings) or generally detracts from the clean appearance of the package. The following examples shall not be classified as defects for unclean:

a. Foreign matter which presents no health hazard or potential package damage and which can be readily removed by gently shaking the package or by gently brushing the package with a clean dry cloth.

b. Localized dried product which affects less than 1/8 of the total surface area of one package face, or an aggregate of scattered dried product which affects less than 1/4 of the total surface area of one package face.

3/ The effective closure seal is defined as any uncontaminated, fusion bonded, continuous path, minimum 1/16 inch wide, from side seal to side seal that produces a hermetically sealed pouch.

4/ Delamination defect classification:

Major - Delamination of the outer ply in the pouch seal area that can be propagated to expose aluminum foil at the food product edge of the pouch after manual flexing of the delaminated area. To flex, the delaminated area shall be held between the thumb and forefinger of each hand with both thumbs and forefingers touching each other. The delaminated area shall then be rapidly flexed 10 times by rotating both hands in alternating clockwise- counterclockwise directions. Care shall be exercised when flexing delaminated areas near the tear notches to avoid tearing the pouch material. After flexing, the separated outer ply shall be grasped between thumb and forefinger and gently lifted toward the food product edge of the seal or if the separated area is too small to be held between thumb and forefinger, a number two stylus shall be inserted into the delaminated area and a gentle lifting force applied against the outer ply. If separation of the outer ply can be made to extend to the product edge of the seal with no discernible resistance to the gentle lifting, the delamination shall be classified as a major defect. Additionally, spot delamination of the outer ply in the body of the pouch that is able to be propagated beyond its initial borders is also a major defect. To determine if the laminated area is a defect, use the following procedure: Mark the outside edges of the delaminated area using a bold permanent marking pen. Open the pouch and remove the contents. Cut the pouch transversely not closer than 1/4 inch ($\pm 1/16$ inch) from the delaminated area. The pouch shall be flexed in the area in question using the procedure described above. Any propagation of the delaminated area, as evidenced by the

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

delaminated area exceeding the limits of the outlined borders, shall be classified as a major defect.

Minor - Minor delamination of the outer ply in the pouch seal area is acceptable and shall not be classified as a minor defect unless it extends to within 1/16 inch of the food product edge of the seal. All other minor outer ply delamination in the pouch seal area or isolated spots of delamination in the body of the pouch that do not propagate when flexed as described above shall be classified as minor defects.

(4) Seal testing. The pouch seals shall be tested for seal strength as required in a, b or c, as applicable.

a. Unfilled pouch seal testing. The seals of the unfilled pouch shall be tested for seal strength in accordance with ASTM F 88-00, Standard Test Method for Seal Strength of Flexible Barrier Materials. The lot size shall be expressed in pouches. The sample size shall be the number of pouches indicated by inspection level S-1. Three specimens shall be cut from each of the three sealed sides of each pouch in the sample. The average seal strength of any side shall be calculated by averaging the results of the three specimens cut from that side. Any average seal strength of less than 6 pounds per inch of width or any test specimen with a seal strength of less than 5 pounds per inch of width shall be classified as a major defect and shall be cause for rejection of the lot.

b. Pouch closure seal testing. The closure seals of the pouches shall be tested for seal strength in accordance with ASTM F 88-00. The lot size shall be expressed in pouches. The sample size shall be the number of pouches indicated by inspection level S-1. For the closure seal on preformed pouches, three adjacent specimens shall be cut from the closure seal of each pouch in the sample. The average seal strength of any side, end or closure shall be calculated by averaging the three specimens cut from that side, end or closure. Any average seal strength of less than 6 pounds per inch of width or any test specimen with a seal strength of less than 5 pounds per inch of width shall be classified as a major defect and shall be cause for rejection of the lot.

c. Internal pressure test. The internal pressure resistance shall be determined by pressurizing the pouches while they are restrained between two rigid plates. The sample size shall be the number of pouches indicated by inspection level S-1. If a three seal tester (one that pressurizes the pouch through an open end) is used, the closure seal shall be cut off for testing the side and bottom seals of the pouch. For testing the closure seal, the bottom seal shall be cut off. The pouches shall be emptied prior to testing. If a four-seal tester (designed to pressurize filled pouches by use of a hypodermic needle through the pouch wall) is used,

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

all four seals can be tested simultaneously. The distance between rigid restraining plates on the four-seal tester shall be equal to the thickness of the product +1/16 inch. Pressure shall be applied at the approximate uniform rate of 1 pound per square inch gage (psig) per second until 14 psig pressure is reached. The 14 psig pressure shall be held constant for 30 seconds and then released. The pouches shall then be examined for separation or yield of the heat seals. Any rupture of the pouch or evidence of seal separation greater than 1/16 inch in the pouch manufacturer's seal shall be considered a test failure. Any seal separation that reduces the effective closure seal width to less than 1/16 inch (see table I, footnote 3/) shall be considered a test failure.

(5) Pouch or bottle leakage. The filled and sealed pouch or bottle shall be examined by submerging in water contained in a desiccator or other suitable container and maintaining a vacuum of 15 inches of mercury for at least 30 seconds. A leak is indicated by a steady progression of bubbles. Isolated bubbles caused by entrapped air are not considered a sign of leakage.

(6) Drop test. Filled and processed pouches or bottles shall be dropped in accordance with ASTM D 5276-98, Standard Test Method for Drop Test of Loaded Containers by Free Fall, from a height of 10 feet. Each pouch or bottle will be dropped twice. Any failure will be cause for rejection of the lot.

B. Packing.

(1) Shipping container and marking examination. The filled and sealed shipping containers shall be examined for the defects listed in table II below. The lot size shall be expressed in shipping containers. The sample unit shall be one shipping container fully packed. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total defects.

TABLE II. Shipping container and marking defects

Category		Defect
<u>Major</u>	<u>Minor</u>	
101		Marking omitted, incorrect, illegible, or improper size, location sequence or method of application.
102		Inadequate workmanship. <u>1/</u>
	201	Contents more or less than specified.

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

1/ Inadequate workmanship is defined as, but not limited to, incomplete closure of container flaps, loose strapping, inadequate stapling, improper taping, or bulged or distorted container.

C. Unit load examination. The unit load shall be examined in accordance with the requirements of DSCP FORM 3507. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

SECTION J REFERENCE DOCUMENTS

DSCP FORMS

DSCP FORM 3507 - Loads, Unit: Preparation for Semiperishable Subsistence Items

DSCP FORM 3556 - Marking Instructions for Boxes, Sacks and Unit Loads of Perishable and Semiperishable Subsistence

FEDERAL STANDARD

FED-STD-595 Colors Used in Government Procurement

NON-GOVERNMENTAL STANDARDS

AMERICAN SOCIETY FOR QUALITY CONTROL (ASQC)

ANSI/ASQCZ1.4-1993 - Sampling Procedures and Tables for Inspection by Attributes

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 479-00 Standard Specification for Annealed Aluminum and Aluminum Alloy Foil for Flexible Barrier, Food Contact, and Other Applications

D 1974-98 (2003) Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Boxes

D 2103-97 Standard Specification for Polyethylene Film and Sheeting

D 5118/D 5118M-95 (2001) Standard Practice for Fabrication of Fiberboard Shipping Boxes

PKG&QAP 20332B
10 October 2003
SUPERSEDING
PKG&QAP 20332A
20 July 2001

D 5276-98 Standard Test Method for Drop Test of Loaded Containers by Free Fall

F 88-00 Standard Test Method for Seal Strength of Flexible Barrier Materials