

## SECTION C

This document covers thermostabilized chicken with vegetables in teriyaki sauce packaged in a polymeric tray for use by the Department of Defense as a component of operational rations.

### C-1 ITEM DESCRIPTION

PCR-C-033A, CHICKEN WITH VEGETABLES IN TERIYAKI SAUCE, PACKAGED IN A POLYMERIC TRAY, SHELF STABLE

### C-2 PERFORMANCE REQUIREMENTS

A. Product standard. A sample shall be subjected to first article or product demonstration model inspection as applicable, in accordance with the tests and inspections of Section E of this Performance-based Contract Requirements document.

B. Commercial sterility. The packaged food shall be processed until commercially sterile.

C. Shelf life. The packaged product shall meet the minimum shelf life requirement of 36 months at 80°F.

D. Appearance.

(1) General. The finished product shall be chicken with mushrooms and diced carrots in teriyaki sauce. The packaged food shall be free from foreign materials.

(2) Chicken. The chicken shall be dices typically produced by 3/4 inch dicer settings and the chicken used shall be from natural proportions. The packaged product shall be practically free of skin, bone or bone fragments, cartilage, coarse connective tissue, tendons or ligaments, and discolored meat. The diced chicken shall have a cooked chicken color.

(3) Teriyaki sauce. The teriyaki sauce shall be a semi-opaque, glossy, medium dark to dark brown color.

E. Odor and flavor.

(1) General. The packaged food shall have an odor and flavor of chicken with vegetables in a teriyaki flavored sauce. The packaged food shall be free from foreign odors and flavors.

(2) Sauce. The sauce shall have an odor and flavor of teriyaki.

F. Texture.

(1) Chicken. The cooked, diced chicken shall be moist and tender.

(2) Vegetables. The vegetables shall be slightly soft to slightly firm.

(3) Teriyaki sauce. The teriyaki sauce shall be smooth.

G. Net weight. The average net weight shall be not less than 92 ounces. No individual polymeric tray shall have a net weight of less than 90 ounces.

H. Drained weight of chicken and vegetables(combined). The average drained weight shall be not less than 41.0 ounces. The drained weight of chicken and vegetables (combined) in an individual polymeric tray shall be not less than 39.0 ounces.

I. Palatability and overall appearance. The finished product shall be equal to or better than the approved product standard in palatability and overall appearance.

J. Analytical requirements.

(1) Protein content. The protein content shall be not less than 9.0 percent.

(2) Fat content. The fat content shall be not greater than 6.0 percent.

(3) Salt content. The salt content shall be not less than 0.8 percent and not greater than 1.3 percent.

**C-3 MISCELLANEOUS INFORMATION**

THE FOLLOWING IS PROVIDED FOR INFORMATION ONLY TO PROVIDE THE BENEFIT OF PAST GOVERNMENT EXPERIENCE. THIS IS NOT A MANDATORY REQUIREMENT.

A. Ingredients/formulation. Ingredients and formulation percentages for the teriyaki sauce may be as follows:

<u>Ingredients</u>	<u>Percent by weight</u>
Water	53.36
Lite soy sauce	21.90
Sugar	9.00
Modified waxy maize starch	5.50
Vegetable oil	4.00
Sherry wine or sherry flavoring <u>1/</u>	3.60
Garlic powder	0.71
Onion powder	0.71
White vinegar	0.62
Ground ginger	0.20
Caramel color	0.15
Salt <u>2/</u>	0.10
Ground red pepper	0.09
Citric acid	0.06

1/ Cooking sherry may be substituted for the sherry wine flavoring.

2/ The total amount of salt in the formula shall be adjusted as necessary to produce a product that complies with the finished product salt requirement.

B. Product preparation. Percentages for product preparation may be as follows:

<u>Ingredients</u>	<u>Percent by weight</u>
Teriyaki sauce	50.0
Diced cooked chicken	33.0
Sliced water chestnuts	7.0
Mushrooms	6.0
3/8 inch diced carrots	4.0

**SECTION D**

**D-1 PACKAGING**

A. Preservation. Product shall be filled into polymeric trays and the trays with protective sleeves shall conform to the requirements of section 3 of MIL-PRF-32004, Packaging of Food in Polymeric Trays. Verification testing and inspection of trays, lids and sleeves shall be in accordance with Section 4 of MIL-PRF-32004 and the Quality Assurance Provisions of Section E of this Performance-based Contract Requirements document.

B. Polymeric tray closure. The filled, sealed, and processed tray shall be securely closed.

**D-2 LABELING**

A. Polymeric tray body. One side of each polymeric tray shall be clearly printed or stamped, in a manner that does not damage the tray, with permanent ink of any contrasting color, which is free of carcinogenic elements. To avoid erroneous marking of trays, the product name, lot number and filling equipment number shall be applied prior to processing. All other tray marking may be applied before or after processing. If these markings are applied along the tray body side (see figure 1 of MIL-PRF-32004), or if applied along the tray body end, are not readily legible in low light conditions, a small, easily legible label detailing product name and number of portions shall be applied along one tray body end, but not over any existing tray markings. 1/

Tray body markings shall include:

- (1) Product name. Commonly used abbreviations may be used when authorized by the inspection agency.
- (2) Tray code includes: 2/
  - Lot Number
  - Filling equipment identification number
  - Retort identification number
  - Retort cook number

1/ As an alternate method, tray body markings may be clearly printed or stamped onto the polymeric tray lid prior to processing, in a manner that does not damage the lid, with permanent ink of any contrasting color, which is free of carcinogenic elements, provided that the required markings are applied onto the tray body after processing.

2/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, 11 October 2000 would be coded as 0285). The Julian code shall represent the day the product was packaged into the tray and processed. Sublotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

B. Polymeric tray lid. The lid shall be clearly printed or stamped, in a manner that does not cause damage. Permanent ink of any contrasting color, which is free of carcinogenic elements, shall be used. As an alternate labeling method, a pre-printed self-adhering 0.002 inch thick clear polyester label printed with indelible contrasting color ink may be used.

- (1) Lid labeling shall include:
  - Product name
  - Ingredients
  - Net weight
  - Name and address of packer
  - Official establishment number (for example, EST 38) or a three letter code identifying the establishment
  
- (2) Lid labeling shall also show the following statements:

TO HEAT IN WATER: Submerge unopened tray in water. Bring water to a boil. Simmer gently 40-45 35-40 minutes. Avoid overheating (tray shows evidence of bulging).

WARNING: Do not heat tray in oven.

TO TRANSPORT AFTER HEATING: Insert tray back into protective sleeve to protect during transport. If sleeve is unavailable, stack trays lid-to-lid with fiberboard pads in between.

CAUTION: Use care when opening as pressure may have been generated within the tray.

TO OPEN: Using a clean knife, cut the lidding around the inside perimeter of the tray seals. 

SUGGESTION: Cut lid along 3 sides and fold over uncut portion. Fold back to keep unused portions protected.

YIELD: Serves 18 portions of approximately 2/3 cup each.

#### **D-3 PACKING**

A. Packing for shipment to ration assembler. Four filled, sealed, processed and sleeved polymeric trays shall be packed in a snug fitting fiberboard box conforming to style RSC-L, type CF, grade 275 of ASTM D 5118, Standard Practice for Fabrication of Fiberboard Shipping Boxes. The sleeved trays shall be placed flat with the first two trays placed with the lids together and the next two trays with the lids together. The box shall be closed in accordance with ASTM D 1974, Standard Practice for Methods of Closing, Sealing, and Reinforcing Fiberboard Shipping Containers.

#### **D-4 UNITIZATION**

A. Unit loads. Unit loads shall be as specified in DSCP FORM 3507, Loads, Unit: Preparation of Semiperishable Subsistence Items.

#### **D-5 MARKING**

A. Shipping containers and unit loads. Marking of shipping containers and unit loads shall be as specified in DPSC FORM 3556 Marking Instructions for Shipping Cases, Sacks and Palletized/Containerized Loads of Perishable and Semiperishable Subsistence.

### **SECTION E INSPECTION AND ACCEPTANCE**

The following quality assurance criteria, utilizing ANSI/ASQC Z1.4-1993, Sampling Procedures and Tables for Inspection by Attributes, are required. When required, the

manufacturer shall provide the certificate(s) of conformance to the appropriate inspection activity. Certificate(s) of conformance not provided shall be cause for rejection of the lot.

A. Definitions.

(1) Critical defect. A critical defect is a defect that judgment and experience indicate would result in hazardous or unsafe conditions for individuals using, maintaining, or depending on the item; or a defect that judgment and experience indicate is likely to prevent the performance of the major end item, i.e., the consumption of the ration.

(2) Major defect. A major defect is a defect, other than critical, that is likely to result in failure, or to reduce materially the usability of the unit of product for its intended purpose.

(3) Minor defect. A minor defect is a defect that is not likely to reduce materially the usability of the unit of product for its intended purpose, or is a departure from established standards having little bearing on the effective use or operation of the unit.

B. Classification of inspections. The inspection requirements specified herein are classified as follows:

(1) Product standard inspection. The first article or product demonstration model shall be inspected in accordance with the provisions of this Performance-based Contract Requirements document and evaluated for overall appearance and palatability. Any failure to conform to the performance requirements or any appearance or palatability failure shall be cause for rejection of the lot.

(2) Conformance inspection. Conformance inspection shall include the examinations and the methods of inspection cited in this section.

**E-5 QUALITY ASSURANCE PROVISIONS (PRODUCT)**

A. Product examination. The finished product shall be examined for compliance with the performance requirements specified in Section C of this Performance-based Contract Requirements document utilizing the double sampling plans indicated in ANSI/ASQC Z1.4 - 1993. The lot size shall be expressed in trays. The sample unit shall be the contents of one tray. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 6.5 for minor defects. Defects and defect classifications are listed in Table I below. The trays shall be heated in accordance with the heating instructions from the tray label prior to conducting any portion of the product examination. The samples for drained weight inspection shall be selected using the same sampling criteria as above.

TABLE I. Product defects 1/ 2/ 3/

Category		Defect
<u>Major</u>	<u>Minor</u>	
		<u>Appearance</u>
101		Bone or bone fragment measuring more than 0.3 inch in any dimension.
	201	Chicken dices not cooked chicken color.
	202	Teriyaki sauce not a semi-opaque, glossy, medium dark brown to dark brown color.
	203	Total weight of skin, cartilage, coarse connective tissue, tendons or ligaments, and discolored meat is more than 1.0 ounce.
		<u>Odor and flavor</u>
102		The packaged food does not have an odor or flavor of chicken with vegetables in a teriyaki sauce.
103		The sauce does not have the odor or flavor of teriyaki.
		<u>Texture</u>
	204	Chicken dices not moist or not tender.
	205	Vegetables not slightly soft to slightly firm.
	206	Teriyaki sauce not smooth.
		<u>Net weight</u>
	207	The net weight of an individual polymeric tray is less than 90 ounces. <u>4/</u>
		<u>Drained weight</u>
	208	The drained weight of chicken and vegetables (combined) in an individual polymeric tray is less than 39.0 ounces. <u>5/</u>

1/ The presence of any foreign material such as but not limited to, dirt, insect parts, hair, wood, glass, metal, or mold or the presence of any foreign odors or flavors such as, but not limited to burnt, scorched, rancid, sour, or stale shall be cause for rejection of the lot.

2/ Finished product not equal to or better than the approved product standard in palatability and overall appearance shall be cause for rejection of the lot.

3/ Dicer size requirement for chicken shall be verified by certificate of conformance. Natural proportions of chicken used shall be verified by certificate of conformance.

4/ Sample average net weight less than 92 ounces shall be cause for rejection of the lot.

5/ Sample average drained weight less than 41.0 ounces shall be cause for rejection of the lot.

B. Methods of inspection.

(1) Commercial sterility. Commercial sterility shall be verified in accordance with USDA/FSIS regulations.

(2) Shelf life. The contractor shall provide a certificate of conformance that the product has a 3 year shelf life when stored at 80°F. Government verification may include storage for 6 months at 100°F or 36 months at 80°F. Upon completion of either storage period, the product will be subjected to a sensory evaluation panel for appearance and palatability and must receive an overall score of 5 or higher based on a 9 point hedonic scale to be considered acceptable.

(3) Net weight. The net weight of the filled and sealed tray shall be determined by weighing each sample unit on a suitable scale tared with a representative empty tray and lid. Results shall be reported to the nearest 1 ounce.

(4) Drained weight. The free liquid in the tray shall be poured off and the remaining contents shall be poured into a flat bottom container. A minimum of three times the volume of a tray of 140° to 190°F water shall be added to the container so as to cover the contents. The contents and water shall be agitated so as to fully dissolve the sauce without undue breakup of the chicken dices or vegetables. The contents shall then be poured into a U.S. Standard No. 7 sieve in a manner that will distribute the product evenly over the sieve. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at such an angle to assure complete drainage of liquid from the product. Drain product for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight of the chicken dices and vegetables shall be reported to the nearest 0.5 ounce.

(5) Analytical. The sample to be analyzed shall be a composite of three filled and sealed polymeric trays which have been selected at random from the lot. The composited sample shall be prepared (see NOTE) and analyzed in accordance with the following methods of the Official Methods of Analysis of AOAC International:

<u>Test</u>	<u>Method Number</u>
Protein	988.05, 992.15
Fat	985.15
Salt	935.47

Test results shall be reported to the nearest 0.1 percent. Any nonconforming results shall be cause for rejection of the lot.

NOTE: The USDA will use AOAC method 983.18 for preparation of the sample.

**E-6 QUALITY ASSURANCE PROVISIONS (PACKAGING AND PACKING MATERIALS, POLYMERIC TRAY)**

A. Packaging and labeling.

(1) Polymeric tray testing. For purposes of clarification, the polymeric tray without the lid will be referred to as the "tray" and the polymeric tray with the lid shall be referred to as the "container". The polymeric tray with protective sleeve and polymeric tray material shall be examined for the characteristics listed in table I of

MIL-PRF-32004, Packaging of Food in Polymeric Trays. The lot size, sample unit, and inspection level criteria are provided in table II below for each of the test characteristics. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot. For rough handling survivability at frozen temperature, polymeric tray survival rate shall be at least 85 percent.

TABLE II. Polymeric tray quality assurance criteria

<u>Prior to processing</u>			
Characteristic	Lot size expressed in	Sample unit	Inspection level
Tray configurations and dimensions	Trays	1 tray	S-1
Oxygen gas transmission rate of tray	Trays	1 tray	S-1
Oxygen gas transmission rate of lid	Yards	1/2 yard	S-1
Water vapor transmission rate of tray	Trays	1 tray	S-1
Water vapor transmission rate of lid	Yards	1/2 yard	S-1
Camouflage	Containers	1 container	S-1
<u>After processing</u>			
Characteristic	Lot size expressed in	Sample unit	Inspection level
Processing	Trays	1 tray	S-2
Rough handling survivability	Test containers	1 container	S-2
Protective sleeve	Containers	1 container	S-1
Residual gas	Containers	1 container	S-1
Closure seal	Containers	1 container	S-1
Internal pressure	Containers	1 container	S-1
Lid opening	Containers	1 container	S-1

(2) Examination of container. The container with protective sleeve removed shall be examined for the defects listed in table II of MIL-PRF-32004 and the labeling defects listed in table III below. The lot size shall be expressed in containers. The sample unit shall be one processed and labeled container. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major A defects, 2.5 for major B defects and 4.0 for minor defects. Two hundred sample units shall be examined for critical defects. The finding of any critical defect shall be cause for rejection of the lot.

TABLE III. Container labeling defects

Category		Defect
Major A	Minor	
101		Polymeric tray lid or body labeling missing, incorrect or illegible.
	201	When a pre-printed self adhering label is used, the label not

adhering to tray lid (for example, label raised or peeled back from edge to corner) or presence of any areas of gaps along the perimeter of the label where the label is not properly adhered.

---

B. Packing.

(1) Shipping container and marking examination. The filled and sealed shipping containers shall be examined for the defects listed in table IV below. The lot size shall be expressed in shipping containers. The sample unit shall be one shipping container fully packed. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total defects.

TABLE IV. Shipping container and marking defects

Category		Defect
Major	Minor	
101		Marking omitted, incorrect, illegible, or improper size, location sequence or method of application.
102		Inadequate workmanship. <u>1/</u>
	201	Arrangement or number of polymeric trays not as specified.

1/ Inadequate workmanship is defined as, but not limited to, incomplete closure of container flaps, loose strapping, inadequate stapling, improper taping, or bulged or distorted container.

C. Unitization.

(1) Unit load examination. The unit load shall be examined in accordance with the requirements of DSCP Form 3507, Loads, Unit: Preparation of Semiperishable Subsistence Items. Any nonconformance shall be classified as a major defect and shall be cause for rejection of the lot.

**SECTION J REFERENCE DOCUMENTS**

DSCP FORMS

DSCP FORM 3507 Loads, Unit: Preparation of Semiperishable Subsistence Items  
DPSC FORM 3556 Marking Instructions for Shipping Cases, Sacks and Palletized/Containerized Loads of Perishable and Semiperishable Subsistence

MILITARY SPECIFICATIONS

MIL-PRF-32004 Packaging of Food in Polymeric Trays

GOVERNMENT PUBLICATIONS

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199) and (9 CFR Parts 1-391)

NON-GOVERNMENTAL STANDARDS

AMERICAN SOCIETY FOR QUALITY (ASQ)

PCR-C-033A  
11 October 2000  
W/CHANGE 02 4 MAR 03  
SUPERSEDING  
PCR-C-033  
29 November 1999

ANSI/ASQCZ1.4-1993 Sampling Procedures and Tables for Inspection by Attributes

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 1974 Standard Practice for Methods of Closing, Sealing, and Reinforcing  
Fiberboard Shipping Containers

D 5118 Standard Practice for Fabrication of Fiberboard Shipping Boxes

AOAC INTERNATIONAL Official Methods of Analysis of the AOAC International

PCR-C-033A  
11 October 2000  
W/CHANGE 02 4 MAR 03  
SUPERSEDING  
PCR-C-033  
29 November 1999

AMSSB-RCF-FN (Valvano/4259)

6 March 2003

TO: DSCP-HRUT (Charya/3832)

Subject: (ES03-068) Document Changes; Various Polymeric Entrees; Reduction of Heating times from 40-45 minutes to 35-40 minutes

1. Natick reviewed several polymeric entrees with regard to reheating times. Some components such as creamed ground beef or pork sausage in gravy may not need the longer heating time period.

2. The polymeric items involved are:

Eggs, Scrambled, Western-style, Polymeric Tray	PCR-E-006	9 Apr 01
Pasta & Italian Sausage, Polymeric Tray	PCR-P-017	14 Feb 01
Eggs, Scrambled, Polymeric Tray	PCR-E-005	11 Jan 01
Chicken Chow Mein, Polymeric Tray	PCR-C-010	18 Dec 00
Lasagna w/Meat Sauce, Polymeric Tray	PCR-L-003	6 Dec 00
Beef Chunks w/Noodles in Sauce, Polymeric Tray	PCR-B-023A	11 Oct 00
Bread Stuffing, Polymeric Tray	PCR-B-028A	12 Oct 00
Chicken w/Vegetables Teriyaki, Polymeric Tray	PCR-C-033A	12 Oct 00
Chili with Beans, Polymeric Tray	PCR-C-034A	12 Oct 00
Pork Sausage in Cream Gravy, Polymeric Tray	PCR-P-014A	11 Oct 00
Cream Gravy w/Ground Beef, Polymeric Tray	PCR-C-040	20 Jun 00
Beef Stew, Polymeric Tray	PCR-B-024	24 May 00
Mashed Potatoes w/Gravy, Polymeric Tray	PCR-M-007	12 Apr 00
Omelet w/Smoked Sausage, Polymeric Tray	PCR-O-006	12 Apr 00
Chicken Breast in Gravy, Polymeric Tray	PCR-C-032	29 Nov 99
Hash, Corned Beef, Polymeric Tray	PCR-H-005	29 Nov 99

3. Natick requests DSCP implement the following change as indicated for the listed documents above. Items that have been deleted from the menus are not included. It is best to modify the contracts in order to get this time change in prior to the next printing of the rollstock film for the lid material.

Sec D, D-2,B Polymeric tray lid: In "TO HEAT IN WATER" after "Simmer gently", delete "40-45" and insert "35-40".

4. The attached document files include the lower heating times and are applicable for pending and future procurements until the document is formally revised or amended.

16 Attachments

DONALD A. HAMLIN  
Team Leader  
Food Engineering Services Team  
Combat Feeding Directorate

CF: NSC:

R Valvano

Acheson

Alashian

Friel

Hamlin

Harrington

Konrady A.

CF: DSCP & SVCs:

Beward

Bankoff

Henry

Malason

PCR-C-033A  
11 October 2000  
W/CHANGE 02 4 MAR 03  
SUPERSEDING  
PCR-C-033  
29 November 1999

Richards  
Swantak  
Trottier  
Valvano

Byrd  
Charette  
Dyduck  
Ferrante

Miller  
Salerno